

# Supporting Lockheed Martin: Skunk Works® Need for Rapid and Reliable Validation

# Safe Lean Thinking

# Industry commitment to safety has been effective at reducing physical injuries, but lives are still being ruined and wasted.

- Suicide rate in construction industry ~ 4 times rate for US general population
  - 25 attempts for every suicide & countless miserable experiences for every attempt

## Lean Thinking Can Help

- Respect for people mindset helps alleviate numerous underlying factors
- What we are doing is important!

# **Topics**

- Introductions
- Burns & McDonnell Lean Journey
- Defining "Fundamental Scope Blocks" and "Scope Activities"
- Application at Lockheed-Martin Skunk Works®
- Next-Generation Applications
- Take-Aways, Key Points & Questions

# **Presentation Team**



John Strickland
Project Innovation Lead
Burns & McDonnell



Ryan Cummings
Project Manager
Burns & McDonnell



**Kris Henry**Facilities Engineering Manager
Lockheed Martin



Dan Koenigsfeld
Director of Aerospace &
Industrial Manufacturing
Burns & McDonnell

# Focus on Integrated Design-Build



1898

YEAR FOUNDED

100%

**EMPLOYEE-OWNED** 

10,000

**PROFESSIONALS** 


90%

**REPEAT BUSINESS** 

\$5B+

**ANNUAL SALES** 

# Key Industries & Markets We Serve



# Burns & McDonnell's Lean Journey



# Burns & McDonnell – Lean Journey

"Overdrive"

**Journey** Map



**Base Concepts (warming up the engine)** 

Visualizing Projects as a Network of Commitments **Customer Conditions of Satisfaction** 

- Internal
- External

Psychological Safety / Inclusion

Systems Thinking (Optimize the Whole)

8 Symptoms of Waste

Broad Acceptance & Use of These Concepts Demonstrated by Leadership Team

"Pull Conversations" Collaborative Problem Solving Basic Scoping App (FSBs & Scope Activities) Simple, Internal Collaborative Design &

Scoping

"Trade Partners" Replace "Subcontractors"

All GFS FCP Lane by end Q2 2021 Part of Formal Career & Business **Planning** 

Formal Pull-Based Scheduling & Coordination

2<sup>nd</sup> Gear

Formal CDS & Advanced Scoping App

Multiple Teams Moving by

Q1 2021


Managing Throughput (Flow)

**Advanced Networking Conversations** 

Pioneers & Future SMEs Emerging

# Pipe Fab Shop Case Study – Traditional Approach


- Extensive design effort over several months
- Formal design documents lots of detail
- Conceptual estimate far beyond allowable cost
- Not much usable content when project had to be abandoned
- Reciprocal frustration



# Pipe Fab Shop Case Study – CDS & SCOPE LIST

- Campus-wide upgrade with multiple moves, expansions and upgrades
- Three "mini" collaborative design and scoping (CDS) sessions
- "Sketch level" drawings supporting Fundamental Scope Blocks (FSBs) and scope activities
- Much better information for customer developed at a much lower cost
- Great team and customer experience

+/- 15% Estimating Accuracy with 2% Engineering



# Skunk Works® Lean Journey



# Lockheed Martin Skunk Works® History

- Notable Aircraft (Collier Trophies)
- F-104 Starfighter (1958)
- USAF A-11 Mach 3 Aircraft (1963)
- F-117 Nighthawk (1989)
- U-2S/ER-2 Dragon Lady (1998)
- JSF/X-35B STOVL (2002)
- F-22 Raptor (2006)
- X-47B (2013)
- Auto CGAS (2018)












# It Ain't Rocket Science... or is it?

- Developmental site = fuzzy requirements
- Several programs competing for limited funding
- Prioritization and simplification is key



Fuzzy front end of the design process (Sanders, Stappers 2008)

# Early Lean Thinkers





Lockheed Skunk Works founder Kelly Johnson (left) and successor Ben Rich (right). (Photos: Lockheed Martin)

# Kelly's 14 Rules: Early Lean Thinking

The Skunk Works Manager must be delegated practically complete controls of his program in all aspects.

**Y** 

Strong but small project offices must be provided both by the military and industry.

The number of people having any connection with the project must be restricted in an almost vicious manner. Use a small number of good people.

aking

A very simple drawing and drawing release system with great flexibility for making changes must be provided.



There must be a minimum number of reports required, but important work must be recorded thoroughly.



There must be a monthly cost review covering not only what has been spent and committed but also projected costs to the conclusion of the program.



The contractor must be delegated and must assume more than normal responsibility to get good vendor bids for subcontract on the project. Commercial bid procedures are often better than military ones.



The inspection system as currently used by the Skunk Works, which has been approved by both the Air Force and Navy, meets the intent of existing military requirements and should be used on new projects.



The contractor must be delegated authority to test his final product in flight. He can and must test it in the initial stages. If he doesn't, he rapidly loses his competency to design other vehicles.



The specifications applying to the hardware must be agreed to well in advance of contracting. The Skunk Works practices of having a specification section stating clearly which important military specification items will not knowingly be complied with and reasons therefore is highly recommended.



Funding a program must be timely so that the contractor doesn't have to keep running to the bank to support government projects.



There must be mutual trust between the military project organization and the contractor, the very close cooperation and liaison on a day-to-day basis. This cuts down on misunderstanding and correspondence to an absolute minimum.

Access by outsiders to the project and its personnel must be strictly controlled by appropriate security measures


Because only a few people will be used in the engineering and most other areas, ways must be provided to reward good performance by pay not based on the number of personnel supervised.



# Putting it all Together




# Developing Fundamental Scope Blocks (FSBs)




# FSBs & Scope Activities


- "What" defined by nouns
- Chunks of scope that provide
   a specific function important to Chilled Water S/R Headers
   Owner and/or project
- Natural points of coordination spanning disciplines and crews
- Means to visualize the "How"



# FSBs & Scope Activities


- Actions always starting with a verb
- Means to visualize
  - "What?", "Who?", and "How?"
  - Complete installation
  - Linkage between FSBs
- Unique discipline, crew and system enables very flexible work breakdown structure (WBS)





### Air Handling Unit

RELEASED FOR DETAILED DESIGN: YES



### **DESIGN REQUIREMENTS:**

### GENERAL:

REUSE EXISTING EQUIPMENT

 MINIMUM MONITORING FOR INTEGRATION TO APOGEE SYSTEM

### FIRE PROTECTION:

PROVIDE DUCT SMOKE DETECTOR IN SUPPLY DUCTWORK

### STRUCTURA

- FOUNDATION PAD AND ANCHORAGE

- (E) WALL OPENING SUPPORT FRAMING

### **DESIGN INFORMATION NEEDS:**

- PROVIDE NEW ELECTRICAL DISCONNECT OR RELOCATE EXISTING?

EXISTING AHU ANCHOR BOLT SIZE AND LAYOUT

### SCOPE ACTIVITIES AND DETAILS:

### DEMOLITION:

. DEMOLISH SUPPLY AND RETURN DUCTWORK AND DRUM LOUVERS

- 2. DEMOLISH DUCT SUPPORTS
- 3. INFILL WALL PENETRATIONS
- 4. DISCONNECT POWER, DUCTWORK AND UTILITIES
- 5. REMOVE AHU AND TEMPORARILY STORE FOR REINSTALLATION
- 6. DEMOLISH AHU PAD

### NEW WORK

### EQUIPMENT PAI

1. EXCAVATE, FORMM AND POUR 4" TALL EQUIPMENT PAD. TOTAL EQUIPMENT PAD THICKNESS TO BE 12" WITH #4 REBAR @ 12" O.C. EACH WAY TOP AND BOTTOM.

1a. EQUIPMENT PAD DIMENSION: 21'L X 9.5'W

### 2. PLACE NEW AHU GROUND ROI

3. PLACE AHU ON EQUIPMENT PAD. ATTACH TO NEW EQUIPMENT PAD WITH SAME LAYOUT, QUANTITY AND SIZE OF BOLTS USED IN EXISTING INSTALLATION. ASSUME TOTAL OF (10) NEW STAINLESS STEEL EXPANSION TYPE ANCHOR BOLTS

 REMOVE RUST ON EXISTING ANCHOR BOLT ANGLE CLIPS AND REPAINT WITH COLD-GALVANIZING TOUCH-UP PAINT.

### FRAMED OPENINGS:

3. FRAME NEW DUCT OPENINGS IN BUILDING, RETURN: 4'-0" x 8'-0", SUPPLY: 3'-6" x 2'-8"

3a. INSTALL C10x15.3 STEEL CHANNEL JAMB POSTS EACH SIDE OF RETURN AIR SUPPLY OPENING ATTACHED TO EXISTING CONCRETE CURB AT BOTTOM AND EXISTING STEEL CHANNEL WIND GIRT AT TOP WITH L4x4x1/4 STEEL ANGLE CLIPS AND (2)-5/8" DIA. BOLTS EACH ANGLE LEG EACH END OF CHANNEL JAMB POSTS.

3b. INSTALL 600S200-54 METAL STUD JAMB POSTS EACH SIDE OF SUPPLY AIR OPENING WITH 600S200-54 METAL STUD HEADER AND SILL, ABOVE AND BELOW THE NEW OPENING RESPECTIVELY. ATTACH METAL STUD JAMB POSTS TO EXISTING STEEL CHANNEL WIND GIRTS WITH L4x4x12 GA. ANGLE CLIPS WITH (4)#12 METAL SCREWS TO METAL STUD JAMB POSTS AND (2)-1/8" FILLET WELDS TO EXISTING STEEL CHANNEL WIND GIRTS. ATTACH HEADER AND SILL STUD MEMBERS TO JAMB POSTS WITH L4x4x12 GA. ANGLE CLIPS WITH (4)#12 METAL SCREWS EACH LEG. 4. CUT WALL FOR NEW DUCT PENETRATIONS

### DUCTWORK & PLUMBING:

6. ROUTE RETURN DUCTWORK FROM WALL OPENINGS TO AHU: 20 LF OF 40x30 DUCTWORK. EXTERIOR DUCTWORK WILL BE INSULATED WITH 2" MINERAL FIBER INSULATION AND INCLUDE WEATHERPROOF JACKET.

7a. ROUTE SUPPLY DUCTWORK FROM WALL OPENINGS TO AHU: 25 LF OF 40x30 DUCTWORK. EXTERIOR DUCTWORK WILL BE INSULATED WITH 2" MINERAL FIBER INSULATION AND INCLUDE WEATHERPROOF JACKET.

7b. ROUTE A TOTAL OF 155 LF OF INTERIOR DUCTWORK, ALL INSULATED WITH 2" MINERAL FIBER BLANKET WRAP. INTERIOR DUCTWORK WILL HAVE FACTORY APPLIED FSK JACKETING: 35 LF OF 40x30 DUCTWORK, 20 LF OF 36x30 DUCTWORK, 20 LF OF 28x30 DUCTWORK, 20 LF OF 28x24 DUCTWORK, 20 LF OF 24x14 DUCTWORK, 7c. INSTALL (16) 30x8 DRUM LOUVERS (BASIS OF DESIGN TITUS DL) EACH WITH A VOLUME DAMPER. 7d. ALL DUCTWORK TO BE GALVANIZED STEEL SHEET METAL.

8. ROUTE NG PIPE DOWN WALL TO AHU: APPROX 30 LF OF 1.5" BLACK STEEL PIPE

9. CONNECT CONDENSATE PIPING TO THE UNIT AND ROUTE TO WASH STATION CONTAINMENT AREA LOCATED IN BUILDING: APPROX 25 LF OF 1 1/4" COPPER PIPE.

### OWER:

10. INSTALL AHU DISCONNECT ON BUILDING WALL: (480V 200A 3PH NEMA 3R RATED FUSED DISCONNECT)

11. ROUTE CONDUIT FROM PANEL MDP TO AHU DISCONNECT/AHU. APPROX 230' LF OF (3)#1/0 & (1)#4 GND IN 2" EMT CONDUIT

12. GROUND PAD FOUNDATION REBAR AND EQUIPMENT ENCLOSURE WITH #6WG TO STRUCTURAL STEEL

### FIRE ALARM

15. ROUTE CONDUIT FROM FIRE ALARM PANEL TO SUPPLY DUCT FOR SMOKE DETECTOR: APPROX


 INSTALL DUCT SMOKE DETECTOR IN SUPPLY DUCTWORK AND PULL CABLE (SIZE) BACK TO FIRE ALARM PANEL.





### Canopy

RELEASED FOR DETAILED DESIGN: YES



### DESIGN REQUIREMENTS:

- ROOFING: SLOPED STANDING SEAM METAL ROOF ATTACHED TO METAL ROOF DECK
- MONOLITHIC SLAB ON GRADE/FOUNDATION FOR CANOPY, DESIGNED FOR FORKLIFT
- EQUIPMENT HOUSEKEEPING PADS/FOUNDATIONS ISOLATED FROM CANOPY PAD/FOUNDATION (COMPRESSIBLE JOINT)
- NO PEAK FENCING REQUIREMENT TO MATCH EXISTING NORTH CANOPY
- GUTTER/DOWNSPOUTS?

- LIGHT FIXTURES: WALL MOUNT FIXTURES
- LIGHTING LEVEL: 25 FC
- CONVENIENCE RECEPTACLES
- GROUNDING: NEW GROUND RING/EQUIPMENT POWER: RELOCATE GOLF CART CHARGERS

FIRE PROTECTION:
- PROVIDE NEW DRY PIPE SPRINKLER SYSTEM FOR PROTECTION OF EXTERIOR. CANOPY AND EQUIPMENT (OVEN(S) AND DUST COLLECTOR) PROVIDE FIRE ALARM MONITORING OF NEW SPRINKER RISER (VALVE TAMPER SWITCH, WATERFLOW SWITCH, PRESSURE SWITCH)

### DESIGN INFORMATION NEEDS:

- DRYING OVEN(S) LAYOUT, SIZE AND WEIGHT
- LIQUID WASTE SYSTEM EQUIPMENT LAYOUT AND SIZES
- DUST COLLECTION LOCATION, SIZE AND WEIGHT
- DEIONIZED WATER LOCATION, SIZE AND WEIGHT
- LOCATION OF GOLF CART CHARGERS

### SCOPE ACTIVITIES & DETAILS:

HEIGHT: 16'-6" @ PEAK. APPROX 1/4"/FT SLOPE

FOOTPRINT: 24" W (MAY CHANGE PENDING LIQUID WASTE DESIGN) X 180 FT LONG

### CANOPY ROOF SYSTEM:

BASIS OF DESIGN AEP SPAN - SPANSEAM METAL ROOFING (REGAL WHITE) OVER COVERBOARD/UNDERLAYMENT ON TOP OF METAL DECKING.

### STRUCTURAL FRAMING:

RE: 30% STRUCT DRAWINGS

FRAMING FOR OVEN AND DUSTCOLLECTION EXHAUST PENETRATIONS?

4a. 8 QTY OF WALL FIXTURES: LITHONIA WALL PACKS

4b. LIGHTING CONTROL: TIME CLOCK

4C POWER VIA (2) #12 & (1) #12 GND IN 3/4°C (250°LF) PANEL LP1

### 5. CHAIN LINK FENCING:

FULL PERIMETER (3 SIDES) @ FULL HEIGHT (15'-6") SECURED TO STRUCTURE. 10' ROLLING GATE AT ACCESS DRIVE. 4" SCH 40 STEEL PIPE FENCE POSTS AT 10'-0" O.C. MAXIMUM ANCHORED AT BOTTOM TO SLAB ON GRADE WITH POST-INSTALLED ANCHORS AND AT TOP TO STEEL CANOPY BEAMS WITH BOLTED VERTICAL SLIP CONNECTIONS.

### 6. CONVENIENCE COMPRESSED AIR

SEE INTERIOR IMPROVEMENTS FSB FOR CONVENIENCE COMPRESSED AIR UNDER CANOPY.


7a, (6) WEATHERPROOF 120V RECEPTACLES THROUGHOUT CANOPY AREA VIA (2) #12 & (1)#12 GND IN 3/4"C (220'LF)

7b. POWER CONNECTION TO AIR COMPRESSOR FROM PANEL MDP/NEW LOCAL 480V 3PH 30A FUSED DISCONNECT VIA (3)#10 & (1)#10GND IN 1°C (150'LF)

8a. GROUND RODS (SPACED EVERY 25') TIED VIA #4/0 AWG ENCOMPASSING CANOPY AND TIED TO STRUCTURAL BUILDING STEEL AND EQUIPMENT VIA #2/0 AWG GREEN INSULATED GROUNDING CABLE.

### 9. SLAB ON GRADE FOUNDATION SYSTEM:

8" THICK CONCRETE SLAB ON GRADE WITH #6 @ 12" O.C. EA. WAY AT CENTERLINE OF SLAB POURED MONOLITHICALLY WITH SPREAD FOOTINGS AND GRADE BEAMS SUPPORTING STEEL CANOPY COLUMNS. AT GRAVITY ONLY STEEL CANOPY COLUMNS. SPREAD FOOTINGS TO BE 18' THICK WITH #5 @ 9" O.C. EACH WAY @ BOTTOM OF SPREAD FOOTING. AT STEEL CANOPY MOMENT FRAME COLUMNS, SPREAD FOOTINGS TO BE 18" THICK WITH #5 @ 9" O.C. EACH WAY TOP AND BOTTOM.




DESIGN INFORMATION NEEDS:

FRAME ASSEMBLY REQUIRED?

LOCATION, SIZE AND WEIGHT OF TANKS

MANUFACTURER'S ANCHORAGE MOUNTING

TYPE/LAYOUT OR SUPPLEMENTAL STEEL SUPPORT



### DESIGN REQUIREMENTS:

### STRUCTURAL:

- DI WATER TANK EQUIPMENT PAD
- DI WATER TANK ANCHORAGE

- DI WATER TANK GROUNDING

- MIXED BED TANK MATERIAL
- 70 GPM OF DI WATER FLOW REQUIRED

1. HOUSEKEEPING PAD: MINIMUM 6" TALL HOUSKEEPING PAD POURED ON TOP OF CANOPY SLAB ON GRADE WITH #4 @ 12" O.C. EACH WAY AT CENTERLINE OF HOUKEEPING PAD. HOUSEKEEPING PAD TO BE ATTACHED TO CANOPY SLAB ON GRADE BELOW WITH CAST-IN-PLACE OR ADHESIVE INSTALLED REBAR DOWELS @ 24" O.C. AROUND PERIMETER OF PAD AND INTERMEDIATE ROWS @ 4'-0" O.C. MAXIMUM EACH WAY. 1a. PRELIMINARY SIZE OF HOUSEKEEPING PAD: 8'-0"x4'-6"

### 2. DOMESTIC WATER PIPING

SCOPE ACTIVITIES AND DETAILS:

2a. SEE INTERIOR IMPROVEMENTS FSB FOR DOMESTIC WATER PIPING. 2b. PROVIDE TAP OUT OF BUILDING AND PROVIDE VALVE AND CAMLOCK FITTING FOR HOSE CONNECTION


### 3. DI TANKS: 2 DI TANKS

3a. PURETEC FLOMAX37 TANKS (BY OWNER). 3b. 2 INCH HOSE: (2) AT APPROX 6 LF AND (1) AT APPROX 10 LF. EACH HOSE WILL HAVE CAMLOCK FITTINGS ON BOTH ENDS (ONE MALE AND ONE FEMALE). 3c. DI WATER TANK ANCHORAGE: ASSUME MANUFACTURER PROVIDES MOUNTING ANCHORAGE LOCATIONS INTEGRATED INTO THE DI TANKS (VERIFCATION W/ MANUF. REQUIRED). ASSUME (4) 3/4" DIA STAINLESS STEEL EXPANSION ANCHOR BOLTS (POST-INSTALLED) REQUIRED AT EACH TANK.

### 4. DEIONIZED WATER

5a. APPROX 100 LINEAR FEET OF 2" DI WATER PIPING. 5b. DI WATER PIPE SHALL BE SCH 80 CPVC WITH CONTINUOUS METAL SUPPORT.

6a. #6 AWG GREEN INSULATED GROUNDING CABLE TO STRUCTURAL STEEL FROM DI




# Results & Next Steps



# Scalability

Fundamental scope blocks can be developed in multi-user relational database

- Portfolio of projects
- Next generation micro-electronics fab with flexibility to fit multiple locations (>1000 FSBs)



# "Next Gen" Advanced Work Packaging (AWP)

### Linking Lean / IPD to Advanced Work Packaging











### Owner & EPC Objectives, Barriers & Continuous Improvement

AWP and Lean both have significant, proven benefits for improved project delivery, and both approaches are still being used as standalone methodologies. In this session, the panel will discuss the current drivers for change, the opportunities presented by an AWP + Lean combined approach.







egister now at www.groupasi.com/awple

# **Key Takeaways**

- Understand "minimum viable product" concept
  - Similar in some respects to "last responsible moment"
- Rapid visualization is very helpful
  - "A picture is worth a thousand words"
- Simple is sometimes better
  - It takes effort to take something complicated and distill it into something sire
- Define the problem before solving it
  - Solving the wrong problem is a waste of time
  - Ready, aim, fire!, not fire, ready, aim!





Send your questions to this team via chat.





# Rate Presentations in the App

Continuous improvement: give presenters your feedback by taking the session evaluation!

- 1. Find the session under "schedule"
- 2. Click on it then scroll down
- 3. Click "core program evaluation"
- 4. Complete the 5-question evaluation

This information will determine the top 5 presentation teams and the top Live Lab





Overall, how valuable was this presentation to you?

Please select an answer:

1 - Not at all2 - Slightly3 - Moderately4 - Very5 - Highly

Next >





In the spirit of continuous improvement, we would like to remind you to complete this session's survey! We look forward to receiving your feedback.



# **Contact Us**

Ryan Cummings, PE

**Burns & McDonnell** 

<u>jrcummings@burnsmcd.com</u>

**Kris Henry** 

**Lockheed Martin Aeronautics** 

Dan Koenigsfeld, PE, LEED® AP BD+C

Burns & McDonnell

dkoenigsfeld@burnsmcd.com

John Strickland

Burns & McDonnell

jpstrickland@burnsmcd.com



Thank you for attending this presentation. Enjoy the rest of the 24<sup>th</sup> Annual LCI Congress!

